

75" Wi-Fi Interactive Flat Panel

40 simultaneous touch points LED ULTRA HD

Integrated touch | Infrared technology | Android 11 20Wx2 integrated speakers | Ambient light sensor ScreenShare Pro license included | USB Type-C Full-Link

HC7520M

75" INTERACTIVE FLAT PANEL Wi-Fi RDM-READY











Zero Gap Technology allows sharper images with better contrast and reduced glare.

Automatic brightness adjustment via ambient light sensor.



Infrared technology touch screen; usable even with gloves or any other solid object.

Anti-glare tempered glass with Mohs 7 4mm thickness.



Integrated 20Wx2 front stereo speakers. Total power 40W



HDMI 4K input Updated interface and electronics 3x HDMI IN, 4x USB 3.0, 2x TOUCH OUT 2x LAN (RJ45 - Autoswitching) 1x USB type-C Full-Link



Quad Core A55 4GB RAM, 32GB ROM **OPS Standard slot**

SI07 Wi-Fi and Bluetooth module included



Remote Display Management Included license (1 year)*

Software Touch Display+ ScreenShare Pro **Perpetual license**





Zero Gap bonding

Direct bonding

The touch panel and the glass surface are bonded without interspace by means of highly transaparent liquid adhesives. There is therefore no empty space between the outer glass and the LCD panel.

Touch Display +

Software Suite



3.0 Teaching Tools dedicated to teachers and students.

Note | Note plus | Capture | AirClass 2.0 | Bytello (Perpetual license included).

ScreenShare Pro included (Perpetual license)



RDM Ready

Remote Display Management




With Chimpa RDM you can remotely control, view and manage the functioning of the Interactive monitor with Android.

Two steps are enough to register the device in your administrative panel.


What are the advantages of Zero Gap?

Thanks to the improvement of the optical refraction between touch and LCD, the monitor will have excellent readability, even in high light conditions, optimized contrast and less reflections. In addition, the monitor will be even more accurate to touch inputs. The absence of air prevents the formation of condensation and the proliferation of mold and bacteria on the screen, thus ensuring maximum hygiene.



Details

Bottom panel



Pens with iron core

Magnetic attachment to the monitor




Front panel



Side panel







USB Type-C Full-Link





USB Type-C Full-Link is based on USB 3.2 Gen 2x2 with a transfer velocity of 20 Gbps thanks to two 10 Gbps lines that work in parallel.



SINGLE INTERFACE

With only one cable it will be possible to transfer 65W, **Audio** and **Video** up to **4K** quality, computer touch signal and network connection between the monitor and compatible devices.

CONNECTION WITH ONLY ONE CABLE

LAN In/out

Autoswitching




Two RJ45 ports

Ine autowitching systems allows to connect the IFP, OPS PC (not included) and any external compatible device in an intuitive way, thanks to interchangeable port in both input/output without external switch or cables.

1000Mbps internet *speed* at full **potential**

CONNECTING DEVICES IT HAS NEVER BEEN EASIER



Note

Interactive board Android software (Perpetual license included)

Application for Android





Simplified
writing tools

Configurable workspace

Advanced additional
drawing tools


Screen and external
webcam recording

Export and direct
sharing in the Cloud



NotePLUS

Software for lectures and presentations (Perpetual license included)
Windows application





Download Software

Subject-specific teaching tools

PowerPoint presentation tool

Export to document format

Auto save | Auto update

Configurable page layout

Speech synthesis of the text

Three different working modes

Hypertext links

Advanced drawing mode

Capture

Recording & Editing video lessons (Perpetual license included)

Windows application



EasiCapture is a complete software for recording and audio/video editing of lectures, video tutorials and video courses. It is an extremely powerful, flexible and easy-to-use solution designed both for teachers, who want to work in an innovative way, for example with a "flipped classroom" approach, and for the entire class when they want to create videos and films of any kind.



Video recording

Screen capture
Capture from peripheral
(webcam, document camera etc.)
Full screen capture
Capture a customized portion
of the screen

Audio recording

Microphone recording Recording from external audio source System audio recording

Video editing

Unlimited tracks
Clip cut
Audio track separator
Video material library
Zoom and video transitions
Insert text | Insert watermark
Insert external files (pictures, audio etc.)
Export in .mp4 format



Bytello


To prepare and share the lessons (Perpetual license included)

Application for Android

Bytello Class

Bytello Class is an Android app that allows the teacher to share the lecture with the students. Each teacher can log-in into the cloud service to create the lessons with its own contents and expand them with the tools made available by the plattform. The lessons are saved on the account of the teacher and they are available at anytime and on any device.

Thanks to the dedicated application installed on the Interactive Flat Panel is it possible to show these lessons to the students that have the possibility to partecipate to the lesson. They also have the possibility to answer to questions with the use of their onw devices, by simply logging in on the website and use the six digit code shown on the application



Animations for the presentation

Save the file on the cloud

Interaction with the students

Magnetic link of the object


2 and 3 dimensions tools

Customizable exercises





Device Slot-in





Software included

Chimpa RDM



Chimpa RDM is a Remote Display Management software solution which allows you to manage, monitor, diagnose and protect devices with Android, used within your organization from data theft and computer intrusions. You need just a few minutes to activate Chimpa and its ease of use makes it suitable even for inexperienced users.

Included license

ScreenShare Pro



Wireless mirroring
File sharing
Multidevice collaboration

Compatible with Windows, MacOS, Linux, iOS and Android. It allows to perform bi-directional mirroring in split-screen mode.

Included license

Remote Display Management



(1 year license included)

Chimpa RDM is a remote device management solution specifically developed for interactive flat panels. Thanks to its advanced features and its versatility, Chimpa RDM can be used in various areas of use:



Meeting rooms



Schools and training centers



Retail and Large distribution



The main features of Chimpa

App and content distribution



With Chimpa you can distribute apps and contents, private APKs, settings and updates from a simple browser panel. In Chimpa Admin Panel you can use official stores or Cloud services, such as Google Drive, Dropbox and OneDrive. You'll just need to perform a few simple steps to send to all, or only to some, the managed devices specific documents and contents or an application to be used.

Profile management and restrictions



Chimpa allows you to manage user profiles, guest profiles and even specific restrictions based on a single device or a certain time slot. Chimpa keeps your company safe from any inappropriate use of devices, thus allowing you to manage separately personal and work data, in full compliance with GDPR at European rules an excellent solution in a BYOD approach.

Kiosk mode e single-App mode



Thanks to Chimpa the flat panel can be set to a specific welcome screen for your school/organization or be configured in Kiosk mode to allow the use of only single application.

Monitoring and remote assistance



Chimpa RDM can monitor and keep record of all hardware and software use reports, notifying any operating anomalies. Furthermore, thanks to the Remote Commands Input section, the supervisor can interact with the monitor as if he/she were physically close to it: this means that it is possible to provide technical assistance and maintenance remotely. Finally, from the Chimpa Admin Panel it is possible to view what the interactive monitor is showing in real time and take control of the device with a simple graphic interface.

Customizable

Specific configuration according to your needs and

Complete

Specific configuration according to your needs and methods of use.

Certified

Chimpa's developer company is the only one in Italy to be an Android Enterprise Mobility Management service provider.

User-Friendly

Clear and intuitive Admin Panel, suitable for users of any level.

Easy Enrollment

HELGI is the only Italian brand able to offer you a complete package right from the first start-up of your devices in just a few taps.

Safe

It protects your organization from inapproriate uses of devices, allowing you to manage the division between personal and corporate data.

Activate your license



Mobile Threat Defense

For the prevention and detection of threats that may affect your Interactive Flat Panel.

The MTD module checks the integrity of the Android Operating System, and data that are stored, ensuring a total protection thanks to an advanced antivirus system and a firewall. They are specifically designed and developed for the Interactive Flat Panel world.

Defend from the threats your Interactive Flat Panel









ScreenShare Pro



Included

ScreenShare Pro is a wireless mirroring, sharing and multidevice collaboration solution. The license (perpetual) allows you to activate the ScreenShare Pro server app of the interactive monitors and there is no limit to the number of client devices (Windows, MacOS, Linux, iOS and Android) that can be connected to it using the same Wi-Fi network.

Among the main features, ScreenShare Pro allows for bi-directional mirroring (from server to client and from client to server) in split-screen mode up to a maximum of 9 devices connected simultaneously.

Remote control of Windows, MacOS and Linux devices through touch input from the monitor, sending of image, audio and video files in real time from client to server, annotation on shared documents.



Mirroring from device to interactive flat panel

(Max 9 devices simultaneously)




Mirroring from interactive flat panel to device

(Max 1 device)



ScreenShare Pro

Included




Technical specification

ScreenShare Pro

Code	HLG-SSP				
License type	Perpetual, to be activated on the monitor's Android OS after installing the .apk server file				
Compatibility	Android (Interactive monitor server), Windows, MacOS, Android, iOS (client device)				
Connection	Wi-Fi on the same network (does not require Internet access)				
Access	With 6-digit PIN				
Security	Display of client devices connected via Master Mode. Ability to accept/refuse connection requests and disconnect managed devices. Ability to define the refresh rate of the connection PIN. Possibility to activate the advanced connection via alphanumeric PIN.				
Split screen	Possibility to view up to a maximum of 9 devices connected simultaneously on the same screen; + function to bring a device to full screen				
Presentations	Support for PowerPoint, KeyNote, PDF slide management; drawing tools and real time annotation on presentations, virtual laser pointer				
		Sharing media files (photo, audio, video) from local library			
		Sharing documents from local library			
	iOS, Android	Audio/video streaming sharing from the device camera			
		Remote control of the contents displayed on the monitor (one client device at a time; possibility to choose between interaction via touchpad mode or motion mode). Supported commands: left click, right click, drag & drop, on-screen keyboard.			
Client tools		Mirroring from monitor to device with remote control of the contents displayed on the monitor (up to a maximum of 9 client devices at a time; supported commands; left click, right click, pinch and zoom, drag & drop, on-screen keyboard.			
		Mirroring from device to monitor via native protocols (AirPlay for iOS, Miracast for Android)			
	Windows, MacOS	Mirroring from monitor to PC with remote controlof the contents displayed on the monitor (one client PC at a time; supported commands: left click, right click, pinch and zoom, drag & drop, on-screen keyboard)			
		Mirroring from PC to monitor with remote control of the contents displayed on the monitorthrough the touch screen interface (up to a maximum of 9 client PC at a time;supported commands:left click, right click, pinch and zoom, drag & drop, on-screen keyboard)			

Motorized carts and stands



Motorized cart for large monitors. Convenient to move between rooms; the space between the wheels allows easy access even with a wheelchair.

Lower panel is optional and customizable to fit with the location style.

Flat panels from 32" to 95" / VESA max 800x600 Height adjustment: $60 \, \mathrm{cm}$

Min / max height from floor (to display centre): 84,7 / 167,8 cm

Maximum weight: 160 kg.



Mobile cart with double telescopic column with a thin profile. Convenient to move between rooms; the space between the wheels allows easy access even with a wheelchair. Display orientation: only landscape.

Flat panel from 32" to 95" / VESA max 800x600 Height adjustment: 65 cm Min / max height from the ground (in the center of the display): 84,7 / 167,8 cm Maximum weight: 100 kg.



Vertical adjustment with crank for correct positioning. Sturdy steel base and shelf for housing accessories. Shelf for webcam.

Flat panel from 60" to 100" / VESA max 1000x600 Height adjustment: 40 cm Min / max height from the ground (in the center of the display): 123 / 163 cm Maximum weight: 100 kg.

Manual carts and stands



Mobile cart with double telescopic column. Adjustable in height only during assembly. Lightweight construction with solid H base.

Flat panel from 32" to 86" / VESA max 800x600 Min / max height from the ground (in the center of the display): 19 / 219,3 cm Maximum weight: 80 kg.



Mobile cart adjustable in height only during assembly. Sturdy steel base and shelf for housing accessories. Shelf for webcam.


Flat panel from 60" to 100" / VESA max 1000x600 Min / max height from the ground (in the center of the display): 135 / 167 cm Maximum weight: 100 kg.

Fixed carts and stands



Fixed wall motorized stand and weight unloading to the ground. Compatible with any type of wall. Designed to get the free distance between the wall and the back of the stand

Flat panel from 32" to 95" / VESA max 800x600 Height adjustment: 65 cm Min / max height from the ground (in the center of the display): 77,8 / 165 cm Maximum weight: 150 kg.



Fixed wall stand and weight unloading to the ground. Ideal for weak or plasterboard walls where it is required to unload the weight to the ground. Quick release system of the display.

Flat panel from 32" to 86" / VESA max 800x600 Height adjustment: 60 cm Min / max height from the ground (in the center of the display): 110 / 170 cm Maximum weight: 90 kg.

that includes webcam + speakers in an all-in-one solution suitable for lar-

ger rooms.



In addition to the supplied software, with HELGIyou can expand the possibility of using the Interactive Flat Panel thanks to some specific accessories. The solutions are designed for the most frequent needs in the corporate/educational fields, to make the Interactive Flat Panel the fulcrum of business/educational collaboration.

nal collaboration. **Wireless Collaboration** The solution dedicated to internal business collaboration and training: with the integrated OPS module, it will be possible to use the display like a real computer with all the features of Windows. H64I7108256 **HLGMOVMIFFLX Corporate Solution** (Standard) The solution for small/medium sized huddle and conference rooms: it includes the display, cart, OPS module and webcam. H64I7108256 **HLGMOVMIFFLX** 61U3100000AM **Corporate Solution** (Advanced) The ideal solution for meeting rooms: compared to the standard 図 version, it includes an A/V soundbar

Customized solutions on request

HMIFMINI-F100


61U3200000AC

H64I7108256

	Code HC7520M	
	Lighting	Direct type LED
	Quality	Grade A
	Display area	165 x 92,8 cm
	Diagonale	75"
	Aspect ratio	16:9
	Resolution	UltraHD 4K
DISPLAY	Color depth	1.07 billion (10 bits)
DISF	Brightness	560 cd/m ²
	Contrast	6.000:1
	Viewing angle	178° V / 178° H
	Refresh rate	60Hz
	Response time	2.5 ms
	Sensors	Ambient light
	Touch technology	Infrared matrix
	Driver	HID
	Simultaneous touch points	Up to 40 (Windows)
	The state of the s	
픙	Input tools	Fingers (even with gloves) or any other passive object
ТОПСН	•	Fingers (even with gloves) or any other passive object
ТОПСН	Input tools	
ТООСН	Input tools Object size	<1.8 mm
ТОПСН	Input tools Object size Response time	< 1.8 mm
	Object size Response time Accuracy	< 1.8 mm < 1.4 ms ±0.5 mm
	Input tools Object size Response time Accuracy Input resolution	< 1.8 mm < 1.4 ms ± 0.5 mm 32767 x 32767
тесн. рата	Input tools Object size Response time Accuracy Input resolution Surface	< 1.8 mm < 1.4 ms ± 0.5 mm 32767 × 32767 Anti-reflective tempered glass 4mm Mohs level 7

Ж	Input	3x HDMI IN (1x front), 1x USB type-C Full-Link (front), 1x VGA IN, 1x PC AUDIO IN, USB 2.0 OTG, 4x USB 3.0 (2x front), 2x TOUCH OUT (1x front), 1x RS232, 2x LAN (RJ45 - Autoswitching)			
NTERFACE	Output	1x Audio Ol	JT, 1x COAX Out		
N	Connectivity Ether		LAN, Wi-Fi, HotSpot, Bluetooth		
	Speaker power	20W x 2	20W x 2		
	OPS slot	Compatible with OPS Standard			
	System version	Android 11			
S	Compatible applications	GSuite, Google Apps, Microsoft Office, Microsoft Teams, Cisco Webex, Zoom, Google Chrome, Mozilla Firefox, Skype			
ANDROID OS	App installation		mpatible with the Android version of action can be deactivated)		
NDN	CPU	Quad Core A55			
4	GPU	Mali G52 GP2			
	RAM	4 GB			
	SSD	32 GB			
	Maximum consumption 245W				
ENERGY	Standby consumption	≤0.5W (Standby)			
H. H.	Lifetime	60.000 hours			
	Operating time	24/7			
RIES	Content of the package	1x EU / UK Power cord (3m), 1x HDMI (3m), 1x USB (5m), User manual, 2x Passive pens, 1x Remote control (batteries included), 1x wall mounting, 1x SI07 (Wi-Fi module Dual Mode)			
ACCESSORIES	Included software	Note (Android), Note ^{PLUS} (Windows) Capture (Windows), ScreenShare Pro (Android) AirClass 2.0 (Android), Bytello			
	Chimpa RDM included license	1 year since	enrollment*		
Cert	tifications		Warranty		
Ene	rgyStar** , ROhS, CE, SGS***		3 years on center		
Admitted languages			Catalan, Czech, Danish, German, Estonian, English, Spanish, French, Croatian, Italian, Hungarian, Dutch, Norwegian Polish, Portuguese, Romanian, Turkish Swedish, Greek, Russian, Arabic, Chinese Japanese, Lithuanian.		

Environmental Conditions							
Operation Temperature	Operation Humidity	Storage Temperature	Storage Humidity	Altitude			
0°C~40°C	10%~90%RH	-20°C~ 60°C	10%~90%RH	below 5000 meters			















www.HELGI-europe.com

HELGI Europe education@helgi-eu

education@helgi-europe.com business@helgi-europe.com

#25112024HC7520M_EN

Distributor