



## Mid to Large Meeting Room Laser Projector with Excellent ROI

### FEATURES

- DLP® technology for vibrant and rich picture quality
- Impressive 9,000 ANSI lumens of brightness, WUXGA resolution, and 20,000:1 contrast ratio for clear, crisp and bright projection
- Long lasting laser light source for constant brightness level and color performance for up to 20,000 hours operations
- Exquisitely vivid colors and natural picture with Rec. 709 color space capacity and HDR support
- Robustic operations thanks to its advanced thermal cooling technology and sealed optical engine
- Installation flexibility is ensured with 7 optional lenses and easy image adjustment
- Loud and clear sound delivered by built-in 2x10W speakers
- Simple one-cable connection thanks to HDBaseT with up to 4K-UHD signal support
- DICOM Simulation Mode for medical training and seminars
- Full compatibility with NovoConnect Solution for wireless presentation and collaboration



## Powerful laser projector for corporate

A smart choice for mid to large corporate meeting rooms thanks to its low total cost of ownership, the DU7295Z laser projector packs tremendous value for companies seeking maintenance-free durability up to 20,000 hours with easy installation and management. DU7295Z ensures superior visibility with 9,000 ANSI lumen brightness and vibrant true-to-life colors with Rec. 709 color space, along with exceptionally quiet 33dB operation. Furthermore, the DU7295Z can be complemented with Vivitek's NovoConnect Solution for wireless presentation and collaboration.



## DU7295Z

## SPECIFICATIONS

Image	<b>Display Type</b>	Single chip DLP® Technology by Texas Instruments
	<b>Brightness</b>	9000 ANSI Lumens
	<b>Native Resolution</b>	WUXGA (1920 x 1200)
	<b>Max. Supported Resolution</b>	4K-UHD (3840 x 2160) @60Hz
	<b>Contrast Ratio</b>	20,000:1
	<b>Native Aspect Ratio</b>	16:10
	<b>Keystone Correction</b>	Vertical +/-30°; Horizontal +/-25°
Optical	<b>Throw Ratio</b>	7 optional lenses from 0.78:1 to 3.0-5.0:1 throw ratio range
	<b>Zoom Ratio</b>	Manual Zoom & Focus
	<b>Offset</b>	Manual Lens Shift
	<b>Lens Shift Range</b>	Manual; Vertical +55%, -15%; Horizontal +/-5%
Features	<b>Features</b>	3D Features, 3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Keypad lock
Compatibility	<b>Video</b>	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L), 4K-UHD
Connectivity	<b>I/O Connection Ports</b>	VGA-In (15pin D-Sub), HDMI Number of Ports v.2.0 (x2), DVI-D, Component (5 BNC) (RGBHV), Composite Video, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (RCA), RJ45 (x2: LANx1, HDBaseTx1), RS-232 (x2: In and Out), 3D-Sync (x2: In and Out), USB A (Power Only), USB B (Service), Remote Jack(wire remote)
General	<b>Lamp Life and Type</b>	Lamp free design. Laser light source lasts up to 20,000 hours
	<b>Dimensions (W x D x H)</b>	470 x 517 x 202 mm
	<b>Weight</b>	25 kg
	<b>Noise Level</b>	40dB/36dB (Normal/Eco. Mode)
	<b>Warranty</b>	Large Venue Laser Phosphor Warranty: 5 Year projector / 5 years or 20.000h on the Laser Phosphor illumination source.(Whichever comes first)
	<b>Standard Accessories</b>	VGA Cable, Lens Cap, Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	<b>Optional Accessories</b>	Remote Control P/N (5041846600)
	<b>UPC Code</b>	DU7295Z-WH: 813097024459; DU7295Z-BK: 813097024541

## OPTIONAL LENSES

Lens Name	Short Throw	Semi Short Throw	Standard Lens	Wide Fix	Wide Zoom	Long Zoom 1	Long Zoom 2
<b>Aspect Ratio</b>	16:10	16:10	16:10	16:10	16:10	16:10	16:10
<b>Throw Ratio</b>	1.10 - 1.30:1	1.25 - 1.60:1	1.54 - 1.93:1	0.78:1	0.77 - 1.10:1	1.93 - 2.89:1	3.00 - 5.01:1
<b>Projection Distance</b>	1-9	1.3-8	1.5-7	0.8-5	1-5	2-20	3-20
<b>Image Size</b>	36-379	39-300	37-211	48-298	43-300	33-481	28-309
<b>Zoom</b>	1.18	1.28	1.25	1	1.42	2.5 - 3.1	1.67
<b>F Number</b>	2.05 - 2.27	2.0 - 2.44	2.0 - 2.09	2.5	2.1 - 2.6	28.5 - 42.75 mm	2.2 - 2.5
<b>Focal Length</b>	16.64 - 19.54 mm	18.65 - 23.85 mm	22.8 - 28.5 mm	11.46 mm	11.45 - 16.32 mm	44.5 - 74.19 mm	44.5 - 74.19 mm
<b>Part Number</b>	5811120054-SVV (VL907G/LNS-5STZ)	5811122743-SVV (VL912G/LNS-5SZ12)	5811120865-SVV (VL906G/LNS-7SZ1)	5811120818-SVV (VL904G/LNS-5FX2)	5811122742-SVV (VL911G/LNS-5WZ2)	5811119237-SVV (VL908G/LNS-7LZ1)	5811120055-SVV (LNS-5LZ2)