
OVERVIEW





| 1. Power connector | 5. Power indicator |
|---------------------|--|
| 2. HDMI 1.4b | 6. NOVO button hole |
| 3. USB 2.0 | 7. Headphone / microphone combo jack (3.5mm) |
| 4. 2x USB 3.1 Gen 1 | 8. Card reader |

Lenovo V15 IIL

PERFORMANCE

Processor

Processor Family

10th Generation Intel® Core™ i3 / i5 / i7 Processor

Processor

| Processor Name | Cores | Threads | Base Frequency | Max Frequency | Cache | Memory Support | Processor Graphics |
|----------------|-------|---------|----------------|---------------|-------|----------------|---------------------------------------|
| Core i3-1005G1 | 2 | 4 | 1.2GHz | 3.4GHz | 4MB | DDR4-3200 | Intel UHD Graphics |
| Core i5-1035G1 | 4 | 8 | 1.0GHz | 3.6GHz | 6MB | DDR4-3200 | Intel UHD Graphics |
| Core i5-1035G4 | 4 | 8 | 1.1GHz | 3.7GHz | 6MB | DDR4-3200 | Intel Iris [®] Plus Graphics |
| Core i7-1065G7 | 4 | 8 | 1.3GHz | 3.9GHz | 8MB | DDR4-3200 | Intel Iris Plus Graphics |

Operating System

Operating System

- Windows® 10 Home 64
- Windows 10 Pro 64
- FreeDOS

Graphics

Graphics

| Graphics | Туре | Memory | Key Features | |
|--|------------|-----------|--------------|--|
| Intel UHD Graphics | Integrated | Shared | DirectX® 12 | |
| Intel Iris Plus Graphics | Integrated | Shared | DirectX 12 | |
| NVIDIA [®] GeForce [®] MX330 | Discrete | 2GB GDDR5 | DirectX 12 | |

Monitor Support

Monitor Support

Supports up to 2 independent displays via native display and 1 external monitor; supports external monitor via HDMI® (up to 4096x2304@24Hz)

Chipset

Chipset

Intel SoC (System on Chip) platform

Memory

Max Memory^[1]

Up to 12GB (4GB soldered + 8GB SO-DIMM) DDR4-2666

Memory Slots

One memory soldered to systemboard, one DDR4 SO-DIMM slot

Memory Type

DDR4-2666

Notes:

1. The max memory is based on the test results with current Lenovo[®] memory offerings. The system may support more memory as the technology develops.

Storage

Storage Support

Up to two drives, 1x 2.5" HDD + 1x M.2 2242/2280 SSD

- 2.5" HDD up to 2TB
- M.2 2242 SSD up to 512GB
- M.2 2280 SSD up to 512GB

Storage Type

Lenovo V15 IIL

Lenovo

| Disk Type | Interface | RPM | Security |
|---|------------------------|------|----------|
| 2.5" SATA HDD | SATA 6Gb/s | 5.4K | - |
| 2.5" SATA HDD | SATA 6Gb/s | 7.2K | - |
| M.2 2242 SSD | PCIe NVMe, PCIe 3.0 x2 | - | - |
| M.2 2280 SSD | PCIe NVMe, PCIe 3.0 x4 | - | - |
| Intel Optane™ Memory with Solid State Storage, M.2 2280 | PCIe NVMe, PCIe 3.0 x4 | - | - |

Removable Storage

Optical

None

Card Reader

4-in-1 card reader (SD, SDHC, SDXC, MMC)

Multi-Media

Audio Chip

High Definition (HD) Audio

Speakers

Stereo speakers, 1.5W x2, Dolby[®] Audio™

Microphone

Single microphone

Camera

0.3-megapixel, fixed focus

Battery

Battery

- Integrated Li-Polymer 30Wh battery
- Integrated Li-Polymer 35Wh battery

Max Battery Life^[1]

- MobileMark[®] 2014: 5.5 hr (30Wh)
- MobileMark 2014: 6 hr (35Wh)

Notes:

1. All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, and/or JEITA 2.0 battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter

65W round tip (wall mount) AC adapter

DESIGN

Display

Display^[1]

| Size | Resolution | Touch | Туре | Brightness | Surface | Aspect Ratio | Contrast Ratio | Color Gamut | Viewing Angle | Key Features |
|-------|--------------------|-------|------|------------|----------------|-----------------|-------------------|----------------|------------------|-----------------|
| 15.6″ | FHD (1920x1080) | None | TN | 220 nits | Anti- glare | 16:9 | - | - | - | - |
| 15.6″ | HD (1366x768) | None | TN | 220 nits | Anti- glare | 16:9 | - | - | - | - |
| 15.6″ | FHD (1920x1080) | None | IPS | 250 nits | Anti- glare | 16:9 | - | - | - | - |

Touchscreen

Non-touch

Notes:

1. California Electronic Waste Recycling Fee

In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product. For more information, go to https://www.calrecycle.ca.gov/Electronics/Consumer

Input Device

Keyboard

6-row, spill-resistant, multimedia Fn keys, numeric keypad

Keyboard Backlight

No support

Touchpad

Buttonless Mylar[®] surface multi-touch touchpad

Mechanical

Dimensions (WxDxH)

362.2 x 251.5 x 19.9 mm (14.26 x 9.9 x 0.78 inches)

Weight^[1]

1.85 kg (4.08 lbs)

Case Color

Iron grey

Surface Treatment

- IMR
- Texture

Case Material

PC + ABS (top), PC + ABS (bottom)

Notes:

1. The system weight varies depending on configurations

CONNECTIVITY

Network

Onboard Ethernet

No Ethernet

WLAN + Bluetooth®

- 802.11ac 1x1 Wi-Fi + Bluetooth 4.2, M.2 card
- 802.11ac 2x2 Wi-Fi + Bluetooth 5.0, M.2 card

Ports^{III}

Standard Ports^[2]

- 1x USB 2.0
- 2x USB 3.1 Gen 1
- 1x HDMI 1.4b
- 1x card reader
- 1x headphone / microphone combo jack (3.5mm)
- 1x power connector

Notes:

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formely USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formely USB 3.1 Gen 2): 10 Gbit/s;

The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed. USB 2.0: 480 Mbit/s;

PSREF Product Specifications Reference

USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s; Thunderbolt[™] 3: 40 Gbit/s; FireWire 400: 400 Mbit/s; FireWire 800: 800 Mbit/s

2. Depending on many factors, actual data transfer speed may be lower than theoretical speed

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in chipset

Fingerprint Reader

No fingerprint reader

BIOS Security

- Supervisor password
- Power-on password
- Hard disk password

SERVICE

Warranty

Base Warranty

- 1-year depot service
- 2-year (1-yr battery) depot service

ENVIRONMENTAL

Operating Environment

Temperature^[1]

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
- Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

1. When you charge the battery, its temperature must be no lower than 10°C (50°F)

CERTIFICATIONS

Green Certifications

Green Certifications

- ErP Lot 3
- RoHS compliant

