

Digital Audio to Stereo Audio Converter (DAC) - 192kHz



The AU-D3-192 is designed to convert either Coaxial or Optical signals from a digital stereo signal to analogue stereo audio. With an advanced 192kHz sampling rate, this unit is particularly useful for enhancing sound reproduction when connecting digital sources to analogue amplifiers.

FEATURES

- Digital Audio to Left/Right Stereo Audio Converter (DAC) with improved 192kHz sample rate for enhanced sound reproduction
- Integrated digital interpolator filter
- Supports digital audio signal (Coaxial/Toslink) input and analogue audio signal (L/R) output
- Accepts uncompressed digital stereo audio input
- Accepts 16 or 24 bit: 32, 44.1, 48, 88.2, 96, 176.4 and 192kHz sample rates



SPECIFICATIONS

Input:	1x RCA (1x Coaxial, 2 Channel LPCM), 1x Toslink (1x Optical, 2 Channel LPCM)
Output:	2x RCA (1x Analogue Stereo (L/R))
Power:	5V/1.2A DC (US/EU standards, CE/FCC/ UL certified)
Dimensions:	42mm (W) x 57mm (D) x 25mm (H)
Gross Weight:	200g
Net. Weight:	210g
Packaging:	Retail Blister Pack

